before you name to 1000-782-5348 before you
Overhead

## Case 09-14814-qwz

## Doc 1240-1

16. ALL EXCAVATION AND GRADING OPERATIONS CONDUCTED WITHIN THE COUNTY LIMITS THALL DOWNED, DUST IS "WATERING, THE DOWNERCHES SHALL GRIVEN ALL REDESSARY DUST CONTROL PERMITS.

- 13. ALL REQUIRED TRAFFIC CONTROL DEVICES SHALL CONFORM TO THE MAIKUAL ON UNIFORM TRAFFIC CONTROL DEVICES (MUTCO), LATEST EDITION.
- N. EUCETT FOR THE MORE PRETONIED UNDER THE TIDMS OF A FRANCHISE, OR MORE PRETONING BY A CONCENSIONAL MEDICE, THE CONTRACTOR SHALL BE RESPONDED FOR MORE THAN MORE AND THE MEDICAL THE MORE OF THE MORE
- 15. THE CONTRACTOR SHALL NOT GRADE MY PARCELS WITH DUTISDE PRIVATE DWILESHIP UNTIL PETRINSPORT TO GRADE HAS BEET GRAFTED BY THE PROPERTY OWNER. 17. AN APPROVED GRADING PLAY SHALL BE ON THE JOB SITE AT ALL TIMES. DEVIATION FROM THE PLAY MUST BE PRECEDED BY AN APPROVED PLAN REYSIGN. . THE CONTRACTOR SHALL NOT GRADE ANY ARMY CORPS OF ENGINEERS (ACCE) 404 ORSIGNATED WASHES UNTIL 404 PERMIT APPROVAL HAS BEEN GRANTED.
- WHERE SOU IS TO BE BENOKED FROM THE STE. THE CONTRACTOR SHALL DESCRIANT THE LICENSTRUM HERE THE TILL MILE PLACED, AND GETMAN LICENSTRUM. THE REAL THE PLACESHIT OF THIS MATERIAL SHALL BE SUBBICT TO THE MATERIAL REALISMENT OF THE MATERIAL REQUIREMENTS AND TENNIS DY THE CONCREMENT SHAD DESCRIBED.
  - ANY RELOCATION, MODIFICATION, ECT, OF EXISTING UTILITIES AND/OR PUBLIC IMPROVEMENTS NECESSITATED BY PROPOSED DEVELOPMENT SHALL BE AT NO EXPENSE TO THE DEDUNTY.

7. A FLOODPLWN USE PERMIT AND RHISHED FLOOR ELEVATION CERTIFICATE ARE REQUIRED YOR ALL PARCELS LICHATED WITHIN THE FEMA DESIGNATED AREAS O SPECIAL FLOOD HAZARD FOR THE 100-YEAR STORM.

DRAINAGE WILL REMAIN IN ITS NATURAL STATE AND WILL NOT BE ALTERED.

OSTURBED, OR DESTRUCTED DIMER THAN AS SHOWN ON THIS DEVELOPMENT PLAN. THE DEFLOPER, ANY SUCCESSORS, AND ASSORS, WILL HOLD THE COUNTY OF MOHAGE, TIS OFFICIASE ENTITIONED, AND AGENT MOHAGE. ANY AND ALL CAMES FOR DAMAGES BEAUTION TO THE USE OF THIS DEFLICATIONED WHATEN BEAUTION TO THE USE OF THIS DEFLICATIONED, TOWARGE, BOSSON DRI DAMAGE CAMES THE COUNTY OF THE COUNT IMPROVEMENTS WILL NOT BE ACCEPTED UNTIL CERTIFIED RECORD DRAWINGS (AS-BULLTS, INCLUDING ALL TEST RESULTS, HAVE BEEN SUBMITTED AND ACCEPTED BY THE COUNTY. HIS SET OF PLAIS HAS BERI REVENDED DRS COMPLIANCE WHY COUNTY 
REQUIREMENTS FROM TO TISSUANCE OF CONSTRUCTION FEMORS, HOWEVER, SLOT 
REVEN SHALL HOT PREVAIL THE COUNTY FROM REQUIRES CONSECTION OF DRS- 
II PLAIS FOUND TO BE IN VIOLATION OF ANY LAWS DODINANCE REVENDE HOW 
PLAIS FOUND TO BE IN VIOLATION OF ANY DESIGNATION OF EMERIES HOW 
REPORTED HE PLAIS TO THE PLAIS FOR THE PLAIS TO PLAIS.

- 10. ALL GRADING SHALL CONFORM TO THE UNIFORM BUILDING CODE, AS ADOPTED AND MODRIED BY MOHAVE OSUNTY. deleterous material as deemed unsuitable by the soils enomeer for use as compacted fill shall be excavated and removed from the site. THE CONTRACTOR SHALL FOLLOW ALL BLUE STAKE LAWS AND NOTIFY BLUE STAKE (1-BOO-STAKE-IT). BEFORE DIGGING.
- 9. ALL MATHOLE FRAME AND COVER GRADE ADJUSTMENTS REQUIRED SHALL MEET THE REQUIREMENTS OF M.A.C. STANDARD DETAIL NO. 422. SHAPING OF ALL SEMER MANHOLE BOTTOMS SHALL BE PER M.A.G. STANDARD SPECIFICATIONS NO. 625.3.1
- UTILITY FAQUITES, SHOWN DR NOT SHOWN IN CONFLICT WITH THIS WORK.
  SHALL BE RELOGATED BY THE CENERAL CONTRACTOR AS REQUIRED. THIS
  ACTIVITY SHALL BE COOKDINATED WITH THE OWNER OF THE UTILITY TO
  PREVIOUS ANY UNIVERSISSARY INTERRUPTION OF SCRUCE. MINIMUM DEPTH OF COVER TO THE TOP OF SEMER PIPE SHALL NOT BE LESS THAN 3 FEET. PER A.A.C. R18-8-E 301. SEMER CLEANGUT SHALL MEET THE REQUIREMENTS OF M.A.G. STANDARD DETAIL NO. 441.

"Ayuelt for Construction Shall be mode of the Bass of Witt Face and the Contractors of Popolosu." At IT Has Called for on the Place but not listed in 80 items shall be considered incorping. San items include but are not milited to, where the occord une-mittald that. Testing salvasing increase, escaling Items someotimes, etc.

WATER METER COVERS SHALL MEET THE REQUIREDIENTS OF MAG. STANDARD DETAIL NO. 310, AND WATER METER BOOKES SHALL MEET THE REQUIREDIENTS OF M.A.G. STANDARD DETAIL NO. 320. ALL TAPPING SLEEVES, VALVES AND VALUE BOXES ON WATERLINES SHALL MEET THE REQUIREMENTS OF W.A.B. SPECIFICATIONS SECTION 630, AND M.A.G. STANDARD DETAIL NO. 340.

NO JUR SHALL RE CONSIDERED COMPLETED WITH, CLIRES, PANDIENTS AND SDEWLIKE HAYE BEER SMETT CLEAN OF ALL DIRT AND DEBRIES AND SURVEY MONUMENTS ARE INSTALLED. NO PANNO CONSTRUCTION SMALL BE STARTED UNTIL ALL UTILITY LINES
ARE COMPLETED & APPROVED UNDER THIS PROPOSED PARE MEE.
BASE COUNSE SMALL NOT BE PLACED UNTIL SUBGRADE HAS BEEN
APPROVED BY THE COUNTY BIGINEER.

THE LICEATION OF ALL WATER VALVES, FIRE HYDRAINTS, AND MANHOLES MUST AT ALL TIMES DURING CONSTRUCTION OF REFERENCED BY THE CONTRACTOR AND MADE AVAILABLE TO THE DOWNTY.

THUTTY FACILITIES, SHOWN OR NOT SHOWN IN CONFLICT WITH THIS WORK SHALL BE RELOCATED IT THE GENERAL CONTRACTOR AS REQUIRED, THIS ACTIVATY SHALL BE CODEONIATED WITH THE OWNER OF THE UTILITY TO PREVENT ANY UNREGESSARY INTERRUPTION OF SERVICE.

EXISTING STREET AND TRAFFIC SIGNS WILL BE MAINTAINED DURING CONSTRUCTION AND RELOCATED BY THE CONTRACTOR AS DIRECTED BY THE PUBLIC WORKS DIRECTOR.

FUTURE DRADE

EXISTING DRADE TOP BACK OF CURB BEGIN

¥8 ± 5 ± 8

EDGE OF PAVEMENT CENTER LINE GRADE FLOW LINE

FOR E ENST

FIRE DEPARTMENT COUNTED
FINISH FLINSH GR
FLOW

HEIH

END OF VERTICAL EDGE OF PAV

HIGH POINT FILISHED GRADE ALL BLOCKING FOR WATER GATE VALVES SHALL MEET THE RECUIREMENTS OF M.A.C. STANDARD DETAIL NO. 301.

- ALL SEWER MAINS SHALL BE PVC SOR—35 SEWER PIPE AND CONFORM WITH ASTM D=2321 STANDARD SPECIFICATIONS.
- II. HE CORPACIOR SHALL ADJAST WALES, MANHOLES, CEMIOLIS, ETE, BOH OID AND TEXT DE PRISSE PANABENT GRACE PER MALA, STRUMOND DETML ZO AND 40A, PROVIDE CONTENTE DECASHIENT FLUSH WITH TRISSI PANEBERT GRACE 19. ALL MANHALES, SHALL BE TESTED BY EPFLITHATION OR VACUUM TEST AA.G. RIB-D-EXIVIDALY. 17. ALL SEMER LINE SEGMENTS SHALL BE TESTED FOR LEAKAGE AS PER ASTM (F-1417-92), REAPPROVED 1898. 17. ALL EXISTING STREET PARKET TO STURBED BY CONSTRUCTION SHALL BE REPLACED IN ACCORDANCE WITH M.A.G. STANDARD DETAIL NO. 200-1 ALL PITTINGS AND VALVES SHALL BE HESTALLED IN ACCORDANCE WITH.
  THE MANUFACTURER'S RECOMMENDATIONS. ALL VALVES ARE TO BE
  PLUMB AND HAVE STRAIGHT AUGUNDIT. WATER MAIN SHALL BE TESTED IN ACCORDANCE WITH M.A.B. SECTION 610-14, AND IN ACCORDANCE WITH M.A.G. SECTION 610.14 FOR DUCTILE IRON PIPE.
- 20. 100 PEPCENT OF ALL SEVER MAINS NEWY CONSTRUCTED SHALL HAVE A DELECTION TEST OF THE TOTAL LENGTH PER A A.C. RIF-9-EXOLO.2.1.
  21. ALL MAHROLES LOCATED WITHIN DRAWAGE EXEMPTS SHALL HAVE WATERTIGHT LIDS PER A A.C. RIF-9-EXOLO.1.0. DAVITACIOR IS 10 FELD VEREY HE ELEVANDOS OF EUSTING ESVERS AT CERTUM, MONTE OF TI-ME, MAD, ORA MITTECETTOM, PROBE TO RECUCERNO WITH ES MANUE OF SEMEN TRESCORING IN THE FALL BETWELL ROTHEL MONTE, MANUE OR SHALL COLSE WARK ON THE CAMBE OF CONTROL FOR METALLICIES THAN THAT SHOWN ON THE TAMB. THE CONTROL TO RECUERTED SEMEN LINE AND CONTROL THE CHRISTICS TON RE-CONTROL TO 20. AL MARG SHALL BE DERECTED FOR BULLTIN 8 AND SHALL BE DERECKEDING OF SUMELY CAMBULTARIES. ALL BEDESCRIFTON OF SUMELY CAMBULTARIES ALL MATES MAINS UN MORE WAS AN HOUSE MATES ALL MATES MARIES AND ALL WAS AND MORE DESCRIFT. 19. ALL WATER PIPES SHALL BE LEAD FREE PER A.A.C. R18-4-504. UTLITY FACILITES, SMOWN DR HOT SHOWN IN COMPLICT WITH THIS WARK,
  SHALL BE RELOCATED BY THE GENERAL CONTRACTOR AS REQUIRED. THIS
  ACTIVITY SHALL BE COXMONATED WITH THE OWNER OF THE UTLITY TO
  PREVENT ANY UNMECESSARY INTERRUPTION OF SERVICE.
- WITH MAY STANDARD DETECTABLE TAPE OR HASING CONTED (GIUS FOR WHITE AND DETECT AND THE HASING AND DETECT AND THE HASING AND DETECT AND THE HASING HASING SALL DETECT AND THE HASING HASING SALL DETECT AND THE HASING HASING BY LAWF LIMITED, REDUIT CAMERIA, OR SMALAR METHOD APPROVED BY JOHN, AND TEXTURE METALL TO. I, CONTRACTOR SHALL INSTALL SEMER SERVICE LINE(S) AS SHOWN ON THE PLANS.
  THE DEPTH OF THE SEWER SERVICE LINE(S), AT THE POINT OF TERMINATION,
  SHALL BE DEEP BROUGH TO SERVICE THE ENTRE LOT IN ACCORDANCE WITH THE
  UNWERDAN PLUMBING CODE. 21. FINAL FLUSHIKA AVD SAMPLIKA AVD TESTIKA SHALL BE PERFORMED AND ACCEPTED PRICH TO PLACING WATERLINES IN SERVICE AS PER M.A.G. STANDARD SPECIFICATIONS 811.45.

. INSTALL M.A.G. STANDARD DETECTABLE TAPE OR PLASTIC CONTEX (BILLE FOR WATER AND GREEN FOR SEWER) #8 WINE FOR ALL WATER AND SEMER LINES.

DATED SEPTEMBER, 2005 AND PREPARED BY:
STAULTY CONSULTANTS, IPIC.
5820 S. EASTERN AVE., SUITE 200
LAS VEGAS MY 48119
(702) 369-9396

STORM WATER POLLUTION PREVENTION PLAN THE GENERAL COMPRACTOR SHALL BE REPOISIBLE FOR ALL NEW TRAFFIC OUTPOL SIGNS AND MARKINGS IN ACCORDANCE WITH THE LATEST EDITION OF THE MAYUAL OF UNIFORM TRAFFIC GONTROL DEVICES (MUTCO).

2.00%

RATE & DIRECTION OF SLOPE CULDESAC STATIONARIS HIGH POINT SWALE DIRECTION

MANUAL

IM TRAFFIC CONTROL
NOT TO
POLYMNYL C

MIDPOINT OF VERTICAL CURVE MARICOPA ASSOCIATION OF GOVERNMENTS MANHOLE

R/W LINE

THE LOCATION OF UTILITIES SHOWN IS BASED LEGAL REST.

INFORMATION ANALYSIS. THE LOCATION AS BASED LEGAL REST.

THE CONTRACTOR SHALL REBEY THE LOCATION OF ALL EXSTING.

UTILITIES AND RUBBED EVALUES PRICE TO COMMENCEMENT OF ANY

CONSTRUCTION BY CALLING.

1. ANALYSIS.

AT LEAST 2 WORKING DAYS IN ADVANCE THE CONTRACTOR SHALL COOPERATE WITH THE UTILITY COMPANIES IN PROTECTING AND MORKING ARGUNO THERE UTILITIES & SERVICE LINES.

CENERAL NOTES

ALL WOOK SHALL BE DONE BY ACCIDIONACE WITH METHAKE COUNTY SEMPAND SPECTRACHIDIS AND GENERAL AND OTHER OUTHITY ASPETTED AND STANDARDS UNLESS OTHERWAYS SPRONGED BY THE CAUNTY BRIDGER, OR UNLESS APPROVED BY THE GAINTY BRIDGER, OR UNLESS APPROVED BY THE GAINTY BRIDGER, OR UNLESS COUNTY BY LEAVING OF THE PLANEWIS AND COMMISSION AND THE BOARD OF SUPERVISORS.

THE CONTINCION SHALL GRAW! A RORT-OF-MAY USE PETMIT FOR MAY WARK
THE CONTINCION SHALL GRAW! A RORT-OF-MAY USE PETMIT FOR MAY WARK
THE PREFERENCE MINIST HE RORT-OF-MAY USE THE CONTINUES HE PETMIT HE RORT-OF-MAY THE CONTINUES HE PETMIT HE PETMIT HE PETMIT HE CONTINUES MINISTRAFF HE CONTINUES WITHIN THE
COULTY MORT-OF-MAY THE CONTINUES WITHIN THE
COULTY RORT-OF-MAY OF CONTINUES WITHIN THE

## CONTROL OF CITILIES BOOK IS BASED UPON EST APPRODUCTION OF CHAIN FROM THE CONTROL AS CHAIN ARE APPRODUCTIONS AND APPROPRIATE THE CONTROL AS CHAIN ARE APPRODUCTIONS AND APPROPRIATE APPROP ALL WORK SHALL BE DOME IN ACCORDANCE WITH THE "LIFEREN STANDARD SPECIAL PRIORISES THE PUBLIC WORKS CONSTRUCTION" AND "VIGEORM STANDARD DETAILS FOR PUBLIC WORKS CONSTRUCTION" SPECIAL SPECIAL SPECIAL SPECIAL PRIORISES AND ASSESSMENT OF THE AMERICAN ASSESSMENT OF THE ACCORDANCE WITH ASSESSMENT OF THE ACCORDANCE SPECIAL SPECIAL

- CONTRACTOR SHALL ACQUIRE & PAY FOR ALL HECESSARY PERMITS.

  WATER MAIN SHALL BE PVC PIPE CLASS 150, MEETING THE REQUIREMENTS OF A W.W.A. C-900. WATER SCHUCE MATERIAL SHALL MEET THE REQUIREMENTS OF M.A.C. STANDARDS SPECIFICATIONS SECTION 755. AT LEAST 2 MEDING DAYS IN ADVANCE. THE CONTRACTOR SHALL COMPRENES IN PROTECTING AND WORKING AROUND THEIR UTUTIES & SERVICE LINES.
- WATER LHES SHALL BE DISINFECTED IN ADCORDANCE WITH A.D.E.Q. ENCORPORATE BULLETIN N.Q. 6.
- TRENCHING AND BACKFILL SHALL MEET THE REQUIREMENTS OF M.A.G. STANDARD SPECIFICATION 601. COMPACTION DENSITIES SHALL BE 95% FROM THE SUBFACE TO 2" BELDW SURFACE. WATER/SENER SEPARATION SHALL MEET THE REQUIREMENTS OF RIG.-K-5000 (LATEST REMSON) SEPARATION SHALL BE A MINIMUM OF 2 VERTICAL, AND 8 HOROZOFIAL.

6. REQUIRED MANHOLES SHALL BE CONSTRUCTED PER M.A.O. STANDARD DETAIL NO. 420.

TREDICHING AND BACKFIL SHALL MEET THE REQUIREMENTS OF M.A.G. STANDARD SPECIFICATION NO. BOT AND A.A.G. R16-5-E201.D.Z.h.i. AND RTB-8-E201.D.h.li. OXMPACTION EDISTIES SHALL BE 96X FROM THE SURFACE. TO 2' BELDW SURFACE.

SHATA HAIN IPPE AND SERVICE SHALL BE PLAC SOR-35, METHIC THE REQUIREMENTS OF AS THE ASSEMBLY MAG SECTION 745, METHICATION SHALL BE IN ACCORDANCE WITH A.S.T.M. STAYDARD SPECIFICATIONS D2321 WATER, 25WER SEPARATION SHALL MEET THE REQUIREMENTS OF MAG STANDARD ENTAILS 4004-1 AND RIGH-4-902C. SEPARATION SHALL BE A MINIMUM OF 2' VERTICAL AND 8' HORIZONTAL

CONTRACTOR SHALL ACCURE & PAY FOR ALL NECESSARY PERMITS

1. ALL EXSTIND STREET PAVEMENT DISTURBED BY CONSTRUCTION SHALL BE REPLACED IN ACCORDANCE WITH M.A.G. STANDARD DETAIL NO. 200

- CURB STOP WITH FLUSHING PIPES SHALL BE CONSTRUCTED AS REQUIRED BY M.A.G. STANDARD DETAIL ND. 39D, TYPE "A"
- I. ALL FITTINGS FOR WATER MAINS SHALL MEET THE REQUIREMENTS OF M.A.G. STANDARD SECTION 752.
- 10. ALL THRUST BLOCKING FOR WATER LINES SHALL MEET THE REQUIREMENTS OF M.A.G. STANDARD DETAIL NO. 380.

  - PO SEAL SHALL MEET M.A.G. STANDARDS SECTION 333,
    CONCRETE CURB AND GUTTER SHALL MEET THE REQUIREMENTS OF M.A.G. STANDARD DETML 220.

THE EXACT POINT OF MATCHING TERMINATION AND OVERLAY, IF MEDESSARY, SHALL BE DETERMINED IN THE FIELD BY THE COUNTY ENGINEER OR AUTHORIZED REPRESENTATIVE.

RIVISHED FLOOR ELEVATION PAD ELEVATION BASE FLOOD ELEVATION

MANUR CONTOUR
TOP OF CURB EXISTING GRADE CONTOUR

CURSTRUCTION OR

DRAHAGE EASO

CUBIC FOOT PER &
CORRUGATED META
COMMERCIAL DRI

He Paning Contractor shall be responsible for the adjustment and placement of Coudrete Collars, Frames, Covers, and valve boces as necessary for a complete job as approved by the county engineer.

- 10 SDEWAKS SHALL BE CONSTRUCTED AS BEQUIED BY M.A.G. STANDARD CONFORM WITH M.A.G. SPECIFICATION 340.

  11. ALL POURED CONCRETE STRACTURES SHALL MEET THE REDUREDHENS OF M.A.G. STD SPECIFICATIONS, SECTION 506.
  - AL ASPHALT CONCRETE PAVENDYT SHALL MEET THE REQUIREMENTS OF M.A.G. STANDARD SECTION 321. . ALL STREET AGGREGATE BASE SHALL MEET THE REQUIREMENTS OF M.A.O. SECTION 310. ONTRACTOR SHALL REPLACE ANY INADEQUATE SUBGRADE MATERIAL WITH APPROPRIATE BACKFILL AS DIRECTED BY THE PROJECT ENGINEER
  - AL BACKFIL, PAKENDYI AND SIBFACE REPLACEMENT SHALL MEET THE REQUIREDMENTS OF MAG. STANDARD DETML NO 200-1 AND MAG. STANDARD SPECKINGATION SECTION 338. ALL TRENCHES SHALL MEET OSMA REQUIREMENTS. ROADWAY EXCAVATION SHALL MEET THE REQUIREMENTS OF MAG. SPECIFICATION 225 FOR "MATERIAG AND M.A.G. SPECIFICATION 250 FOR "MATERIAG AND M.A.G. STANDARD SPECIFICATION 301 FOR SUBGRADE PREPARATION. AT LEAST 2 MORNING DAYS IN ADVANCE. THE CONTRACTOR SHALL CONDERANTS AND THE THE THE PROPERTIES AND MORNING THERE UTILITIES & SERVICE LINES. THE EXACT LOCATION OF LITLINES SHOWN IS BASED LIPED BEST HE CONTROL TO SHALL BEET THE LOCATION AS SHOWN ARE APPROXIMATE. THE CONTROL TO SHALL VERS Y HE LOCATION OF ALL EXISTING UNITLINES AND BURED CASHES PRIOR TO COMMENCEMENT OF MAY CONSTRUCTION FOR ALL VERS YOUR CONSTRUCTION OF MAY CONSTRUCTION OF YOUR PROPERTY OF MAY CONSTRUCT TO COMMENCEMENT OF MAY CONSTRUCT TO CONSTRUCT TO COMMENCEMENT OF MAY CONSTRUCT TO COMMENT OF MAY CONSTRUCT TO COMMENCEMENT OF MAY CONSTRUCT TO COMMENT OF MAY CONSTRUCT TO COME. TEMAN PLANDS ZONE
    TEMAN PROPRIED OF 202 2000
    A PROPRIED OF THE 202 2000
    STEEL SCHOOL THE 202 2000
    A PROPRIED OF THE 202
    A PROPRIED

# ALL MORE SHALL BE DONE IN ACCOMMEND IN THE "LIMITION STANDARD UNILESS OTHERWISE HOUDD OIL HE PLANS. WILLIAM SHALL BE DONE IN ACCOMMEND OF GENERALIZING (M.A.G.). UNLESS OTHERWISE HOUDD OIL HE PLANS. ALL CONSTRUCTION SHALL CONFORM WITH THE SOILS BEPORT PREPARED BY: AMERICAN SOILS BIGHERPHING, LLG. BIGHERPHING, LLG. BATED: 12 SEPTEMBER 05 PROJECT No.: 1080—3EC SITE CHADING

ENGINEERS NOTES

42874 STEVEN A HADEL

PREPARED 8Y: STAILEY CONSULTANTS, INC. SBZID S. EASTERN AVE., SUITE ZDO LAS VEGAS NY 89119 (702) 369-9396

AL DENSITY REQUIREMENTS FOR STREETS SHALL MEET THE REQUIREMENTS OF M.A.G. SPECIFICATION 301 AND M.A.G. SPECIFICATION 301 AND M.A.G. SPECIFICATION 501 FOR ALL WITHER MID SENSE TREMOVES. COMPACTION DENSITIES SHALL BE 95% FROM THE SURFACE TO 2" BELOW SURFACE.

ORIGINAL STUDY DATED: OCTOBER 2005 UPDATE DATED: MARCH 2005 DRAINAGE REPORT

CONTINUED CONTINUED CAREAS THAT IS ACCIDIANCE WITH COMEMANY CONTINUED CONTIN THE CONTRACTOR SHALL VERIEV ALL SITE CONDITIONS AND DIMENSIONS, AND SHALL NOTIFY THE ENGINEER OF ALL DISCREPANCIES PRIOR TO THE COMMENCEMENT OF WORK.

i. See landsdape plans for landscaping and distre irrigation. ADD 2500' TO ALL ELEVATIONS < 500' ON THESE DRAWINGS TO GET ACTUAL ELEVATION.

8. SEE OFF-SITE ROADWAY IMPROVEMENT PLANS BY STANLEY CONSULTANTS FOR PERIMETER ROAD GRADING. 5. SEE GOLF COURSE PLANS BY TED ROBINSON FOR COLF COURSE GRADING

PRELIMINARY ISSUE FOR REVIEW NOT FOR CONSTRUCTION 03-10-06

PULL BOX

DOSTING STREET LIGHT SERVICE POINT NAIS JOLS \_90 STREET NAME SIGN

ROPOSED BARRICADE

### PVC WATER Įю Î ₽ 🗒 \varTheta 🕞 **#** # NOTE: ALL ABBREVIATIONS SHOWN ON THIS LEGGID MAY NOT APPEAR ON THIS SET OF DRAWINGS. STORM DRAW MANHOLE STORM DRAW INLET STORM DRAW PIPE INDIVIDUAL PRESSURE REDUCING 48" SANITARY SENER MANHOLE 3/4" WATER METER W/ 1" WATER LATERAL 2" BLOWDFF ASSEMBLY \*\* SERVICE LATERAL W/4" WYE BIDIYIDUAL SEWER BACKWATER VALVE PVC SANITARY SENER MAIN (PUBLIC) CROSS BATE VALVE TEE W/VALVE PVC WATER MAIN (PUBLIC) PROPUSED FIRE HYDRAUT EXISTING FIRE HYDRANT 45 90 BEND ANTER RHODES HOMES ARIZONA, LLC GOLDEN VALLEY RANCH NOTES 2 OF 68 SHEETS SCI PROJECT# 18476

j

EXISTING SIGNAL WITH UTILITY POLE

IISCELLANEOUS SICH

TOP OF SLOPE

CUT OR FILL SLOPES S/W RAMP EX CURB & GUTTER

DRADE BREAK

EASEMENT LINE

PERIMETER BLOCK WALL

EDGE OF PAVEMENT EXISTING EDDE OF PAVENER CENTER LINE

DRIVEWAY

A IJ 0

EX STREETUGHT

100 WATT LUMINAIRE 250 WATT LUMINAIRE



SCALE (H) NONE					
SCALE (V) NONE					
DRAWN BY GA/CD/RM					
CHECKED BY DB/SH					
DATE D3-10-06					
Jan 10 10 10 10	DEV. NO.	DEMONSTRA	CHAMB BY	AMONO I	DATE

SNOLLVATERBY

THAS OF THE PARTY OF THE PARTY